

# Product data sheet

## 9023 M-1

EAN-No. 4000896227112



4-pieces ·  $\frac{6.3}{16}$ ,  $\frac{10}{16}$ ,  $\frac{6.3}{16}$



### Application:

With the open 17 mm inside hexagon it is also possible to work on extra long threads

- Can be used for  $\frac{6.3}{16}$ ,  $\frac{10}{16}$  and  $\frac{6.3}{16}$  by replacing the ratchet heads

#### Contents:

- Push-through ratchet
- Square socket  $\frac{1}{4}$ " (6.3 mm)
- Square socket  $\frac{3}{8}$ " (10 mm)
- Hexagon screwdriver bit socket  $\frac{1}{4}$ " (6.3 mm)

- Short design
- Reduced vibrations
- Exhaust air is guided through the handle
- For manual retightening with torque values 70 Nm
- Air connection inlet: inside thread (IG) 12.91 mm ( $\frac{1}{4}$ " )
- Coupler plug: Nominal size 7.2 (included)
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 93.8 db(A) Lp W
- Vibration acceleration: 3.20 m/s<sup>2</sup>
- Forward and reverse: single-stage (right/left)
- Cold insulated handle
- Output:  $\frac{6.3}{16}$ ,  $\frac{10}{16}$ ,  $\frac{6.3}{16}$
- Dimensions: 159 mm
- Net weight: 0.48 kg
- For impact operation
- Tightening torque maximum [Nm]: 54 Nm
- Sound pressure level: 82.8 dB(A) Lp A
- Revolutions per minute: 400
- Air requirement: 84 l/min (1.4 l/sec)

### "Mini" pneumatic tools range

- Innovative 5-slat concept for even more power than conventional drives
- High reliability and continuous operation
- Number of tools: 4


Handle	Cold insulated handle
Order Number	9023 M-1

# Product data sheet


## 9023 M-1

EAN-No. 4000896227112



9023M-1-020 •  3/4



9023M-1-021 •  9/8



9023M-1-B • 