Product data sheet 9212-1000 EAN-No. 4000896222711



Loosening torque maximum [Nm]: 1400 Nm · 125 1/2



Application:

Work independently

- High efficiency thanks to brushless motor
- Basic unit cordless impact wrench (without rechargeable battery, charger, case)
- 18 V · 5 Ah (Ampere hours)
- Suitable for continuous operation
- Robust machine housing
- There are three power stages to choose from for torque acceleration:

Stage 1 180 Nm at 0 - 400 rpm (0 - 800 impacts/min)

Stage 2 400 Nm at 0 - 800 rpm (0 - 1600 impacts/min)

Stage 3 1000 Nm at 0 - 1800 rpm (0 - 2200 impacts/min)

- · Illumination of the work area before the output begins to move
- Compatible with HAZET rechargeable batteries 9212-02 and 9212-05
- Dimensions including rechargeable battery: 278 x 230 x 89.5 mm
- Including belt clip, attachable on both sides

• Brushless DC motor (BLDC)

- Longer service life, less wear, no need to change the carbon brushes
- High efficiency and hence less battery consumption
- More compact motor enables smaller installation dimensions
- Sound power level: 112 db(A) Lp W
- Vibration acceleration: 17.80 m/s2
- Loosening torque (maximum) determined with screw size M: 24
- Forward and reverse: multi-stage (right/left)
- Output: 125 1/2
- Net weight: 3.64 kg
- For impact operation
- Tightening torque maximum [Nm]: 1000 Nm
- Loosening torque maximum [Nm]: 1400 Nm
- Sound pressure level: 101 dB(A) Lp A

Product data sheet 9212-1000 EAN-No. 4000896222711



• Revolutions per minute: 0 - 1800

Do you know - Li-Ion batteries:

- · Do not have any memory effect
- Consist of cells with 3.6 V each
- After full charge they have a higher voltage than 3.6 V i.e. 5 cells each 3.6 V = 18 V but after full charge a peak voltage of up to 20 V is possible
 - Attention: For a longer lifetime of the battery please store it charged up to 50 to 80 % only
- Have an energy density which is twice as high as nickel cadmium batteries, for example
- Have a nominal voltage three times higher than a nickel metal hydride battery
- Require multiple complete charging cycles to reach full capacity

Order Number 9212-1000