

## **Product information**

## 77 32 130 ESD

## **Electronics Diagonal Cutters ESD**

## With box joint

DIN ISO 9654 DIN EN 61 340-5





- and index fingerLess physical effort due to very high transmission ratio
- Pointed head, with small bevel
- Load-optimised for a more direct feel when working
  Low-friction double spring for gentle and even opening
- The mirror polish in combination with a fine oil film provides rust protection - no circuit faults caused by peeling chrome from plated tools
- Cutters additionally laser hardened, cutter hardness at least 62 HRC



MM 🖾 🦯

General	
Article No.	77 32 130 ESD
EAN	4003773089193
Head	mirror polished
Handles	with multi-component grips
Weight	80 g
Dimensions	130 x 80 x 17 mm
Standard	DIN ISO 9654 DIN EN 61 340-5
REACH compliant	does not contain SVHC
RoHS compliant	not applicable
Technical details	
Cutting capacities medium hard wire (diameter)	Ø 1.3 mm
Schneidwerte harter Draht (Durchmesser)	Ø 0.6 mm
Cutting capacities soft wire (diameter)	Ø 0.3 – 2 mm
Jaw length (B)	16.2 mm
Jaw thickness (joint) (D)	8.5 mm
Head width (A)	13 mm
Cutting edge length mm (C)	16.2 mm
ESD	yes

technical change and errors excepted