

 For cutting thin walled plastic pipes (conduit plastic pipes) and flexible hoses, also with fabric reinforcement, of plastic and rubber up to Ø 25

Ergonomically shaped handles made of glass fibre reinforced plastic

Product information

90 20 185

KNIPEX PlastiCut®

Cutter for flexible hoses and plastic conduit pipes. Not suitable for cutting cables

KNIPEX 10 20 155 Main informer

MW

General

Article No.90 20 185EAN4003773067122Headchrome-platedHandlesglass fibre reinforced plastic handlesWeight172 gDimensions185 x 70 x 25 mmREACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities (diameter)Ø 25 mmCutting edge length mmØ 25 mm		
Headchrome-platedHandlesglass fibre reinforced plastic handlesWeight172 gDimensions185 x 70 x 25 mmREACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities (diameter)Ø 25 mm	Article No.	90 20 185
Handlesglass fibre reinforced plastic handlesWeight172 gDimensions185 x 70 x 25 mmREACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities (diameter)Ø 25 mm	EAN	4003773067122
Weight172 gDimensions185 x 70 x 25 mmREACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities (diameter)Ø 25 mm	Head	chrome-plated
Dimensions185 x 70 x 25 mmREACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacities (diameter)Ø 25 mm	Handles	glass fibre reinforced plastic handles
REACH compliant does not contain SVHC RoHS compliant not applicable Technical details Cutting capacities (diameter) Ø 25 mm	Weight	172 g
RoHS compliantnot applicableTechnical detailsØ 25 mm	Dimensions	185 x 70 x 25 mm
Technical details Cutting capacities (diameter) Ø 25 mm	REACH compliant	does not contain SVHC
Cutting capacities (diameter) Ø 25 mm	RoHS compliant	not applicable
	Technical details	
Cutting edge length mm Ø 25 mm	Cutting capacities (diameter)	Ø 25 mm
	Cutting edge length mm	Ø 25 mm

mm / 1"

•

•

•

Exchangeable blade

With opening spring and locking device

technical change and errors excepted



With replaceable blade





